COMPASS Checklist 2006

| Date: | 2006 | Night | _ Day | Evening |
|--|-----------|-----------------|---------------------------------------|-----------------------------|
| Shiftlea | ader: | | | |
| to be performed twice | per shift | | | |
| to so performed twice | per siniv | | | |
| General Checks | | | Time | |
| First run number after checklist done: | | | 1 11116 | ; |
| Print and check Beam Line Magnet Status and Spill | | | (not | yet available) |
| Print and check STATUS GENERAL | | | , | yet available) |
| Check Murphy for every run | | | (1111 | g |
| Print Booky twice and check every run | | | ≈ 2 a | and 6 hrs after shift start |
| Print and check Scaler 48 hr booky once per shift | | | (not | yet available) |
| Print and check masked alarms in slow control | | | | |
| Print and check channels OFF and channel settings lists | | | ists how | many channels off? |
| check $DC/\mu\Omega$ control is displayed on up. right screen | | | | |
| run check_trigger: che | | | | |
| run check_daq: look f | | s, call DAQ exp | ert | |
| Reference Run number | | . – 6(5) | | |
| SM2-NMR reading (Scope & history in DCS) 1.5935 ± 0.0005 _ / _ | | | | |
| SM1-Hall (DVM) + Value: (59.63 ± 0.04) / - Value: (59.70 ± 0.04) | | | | |
| DAQ Barrack, check no audible alarm T below $\simeq 30^{o} \mathrm{c}$ | | | | |
| RICH Gassystem : PD0 – PD7 flow meters $> 50 \text{ l/h}(24.5.03)$: | | | | |
| If not ok: switch off PD HV and call expert | | | | |
| Check the blue compressor: it must be running (vibrations): | | | | |
| If not on: switch off PD HV and call expert | | | | |
| MW2 Gassystem | | | | |
| Check 6 input flow meters: 10-35 l/h 1 - 6: | | | | |
| Check 6 output bubblers: all bubbling? 1 – 6: | | | | |
| If some are not bubbling: call expert | | | | |
| Mixture: CH_4 : ≈ 16 Ar: ≈ 100 safety bubbler should not bubble more than $0.1 - 1$ hz | | | | |
| | | | · · · · · · · · · · · · · · · · · · · | |
| MW1 and RICH Wall Gassystem Check 8 MW1 input flow meters $\simeq 10 - 20 \text{ l/h}$ $1 - 8$ | | | | |
| Check 8 RW (ch1-ch8) input flow meters $\simeq 5 - 15$ l/h $= 1 - 8$ | | | | |
| | | | | |
| MM and DC Gassystems Check 6 MM output bubblers: all bubbling? 1 – 6 | | | | |
| Check 3 DC output bubblers: all bubbling? $1-3$ | | | | |
| Check that security bubblers are NOT bubbling (lower row): | | | | |
| RICH light gas pipe: He system | | | | |
| Check 2 flow meters: #8: Range 6 < flow < 16 l/s: #10 Range 10 < flow < 20 l/s: | | | | |
| Note: #8 close to lower limit | | | | |
| 1 11 - 01000 00 1011 | | | | |

```
MW2 Gas Control Modules (green rack)
MW2: Ar 90
                     CH_4 30
If flows deviate by more than 2 units: Press "RESET" button on control unit
PLC3 (W45, MM, DC, RWall/MW1) (do not care about MW2 here)
press "Logo" to get started (Note: press "Esc" to get back one menu)
Check that W45, MM, DC, RWall/MW1 Battery are ON
If something is not ON, call expert and switch off HV of chamber concerned
Press "MM": Check "Flowmeters: ON"?
                                              check Ne flow: 6 \pm 1 l/h:
Press "Curves" (R8): Check "Actual Value" C<sub>2</sub>H<sub>6</sub> is 10%
Press "Next" (R8): Check "Actual Value" CF<sub>4</sub> is 10%
Press "DC": Check "Flowmeters: ON"? check Ar flow: 7 \pm 2 \text{ l/h}:
Press "Curves" (R8): Check "Actual Value" C_2H_6 is 44 \pm 1\%
Press "Next" (R8): Check "Actual Value" CF<sub>4</sub> is 10%
Press "W45": Check "Flowmeters: ON"?
                                                     check Argon flow: 80 \pm 20 \text{ l/h}
Press "Curves" (R8): Check "Actual Value" \overline{\text{CF}_4} is 10%
Press "Next" (R8): Check "Actual Value" CO<sub>2</sub> is 5%
Press "Rich Wall": Check "Flowmeters: ON"?
Press "Curves" (R8): Check "Actual Value" CO<sub>2</sub> is 30%
Press "Logo" to finish
Flows Silicon: 3 flow meters (between grey rack with bubblers and green rack)
                           Si02: \approx 350 \text{ l/h}
                                                   Si03:\approx 350 l/h
Si01: \approx 500 \text{ l/h}
PLC2 (STRAW, MWPC, GEMs, CSI)
press "Logo" to get started (Note: press "Esc" to get back one menu)
Check that Straw, MWPC, GEM, CSI Battery are ON
If something is not ON, call expert and switch off HV of chamber concerned
Press "Straw setting": Check "Flowmeters: ON"?
Check Ar flow: 95 \pm 5 \text{ l/h}:
                              CF_4 flow: 12 \pm 1 l/h:
                                                              CO_2 flow: 12 \pm 1 l/h:
Press "CF<sub>4</sub> mixture curve" (R6): Check "Actual Value" CF<sub>4</sub> is 10%
Press "Esc", then "CO<sub>2</sub> mixture curve" (R8): Check "Actual Value" CO<sub>2</sub> is 10%
Press "MWPC setting": Check "Flowmeters: ON"?
Press "CO<sub>2</sub> mixture curve" (R6): Check "Actual Value" \overline{\text{CO}_2} is 6%
Press "Esc", then "CF<sub>4</sub> mixture curve" (R8): Check "Actual Value" \overline{\text{CF}_4} is 20%
Press "GEMs setting": Check "Flowmeters: ON"?
Check Ar flow: 30 l/h: ____ CO_2 flow: 13 l/h:
Press "CO<sub>2</sub> mixture curve" (R6): Check "Actual Value" CO<sub>2</sub> is constant at 30%
Press "Logo" to finish
GEMs: flow to GM01 to GM11: 3 < flow < 5 l/h (upper edge of ball)
Knock on the glass cover if the ball does not move
MWPCs
MWPCs input flow meters: between 5 and 17 units
Straws
Flow meters 1-3, 5-10, 12-17 with 60 l/h?
All flowmeter readings between red labels?
W45 Ch 1: 50 – 60 l/h
                              Ch 2: 50 - 60 \text{ l/h}
                                                       Ch 3: 50 - 60 \text{ l/h}
      Ch 4: 50 - 60 \text{ l/h}
                          Ch 5: 50 - 60 \text{ l/h}
                                                       Ch 6: 50 - 60 \text{ l/h}
```